

GLADKIKH, A.N.; MASLENNIKOV, N.I.; FARAFONOV, P.P.

Automatic production lines for bolts and screws. Kuz.-shtam. proizv.  
3 no.1:9-11 Ja '61. (MIRA 14:1)  
(Forging) (Assembly line methods)

GLADKIKH, A.N., kand.tekhn.nauk; MASLENNIKOV, N.I.; FARAFOV, P.P.

Automatic and continuous lines for the hardware manufacture.

Mashinostroitel' no.12:8-9 D '61.

(MIRA 14:12)

(Machine tools--Technological innovations)

(Automation)

FARAFONOV, V. K.

112/105

539.414

Ultimate Stress in the Torsional  
Deformation of an Isotropic  
Material

Dokl. Akad. Nauk  
93(4), 651-654  
1953

F. P. Rybalko, V. K. Farafonov

U. S. S. R.

Index  
Aeronautics  
May 1954  
Strength of  
Materials

Experiments are described intended to verify the theory of Yakutovich that failure of a material under load is always due to normal stresses, and that the conventional classification into 'rupture' failure and 'shear' failure does not represent the true microstructural development. In a perfectly isotropic substance such as perspex, the fracture surfaces in fact show initial cracks oriented at 45 degrees to the axis, i.e. due to normal stresses. The observed, apparent shearing failure, is due to the secondary appearance of macroscopic cracks; the fracture face consists of a number of radiating 'facets' in each of which rupture has taken place under normal stress. The theory is applicable, with suitable corrections, to crystalline and anisotropic materials. (Bibl. 4)

*Uncl State U. in. Gorkiy (for Farafonov and Rybalko)*

L 19304-63

ACCESSION NR: AR3006904

EMP(q)/EMI(m)/BDS

ASD/AFTTC

JD  
S/0137/63/000/007/1019/1019

SOURCE: RZh. Metallurgiya, Abs. 71126

AUTHOR: Shteynberg, M. M.; Molchanova, I. P.; Farafonov, V. K.; Kodes, Ye. S.

TITLE: Investigation of the kinetics of austenite decomposition and the thermal stability of EI-415 steel

CITED SOURCE: Sb. Metallovedeniye i liteyn. proiz-vo Sverdlovsk, 1960, 50-62

TOPIC TAGS: austenite, steel, EI-415, thermal stability, carbide, ferrite, austenitization

TRANSLATION: The kinetics of the decomposition of supercooled austenite (A) of steel EI-415, with composition (in %): C 0.19, Si 0.21, P 0.008, Ni 0.24, Cr 2.47, W 0.42, Mo 0.51, V 0.7, was investigated by the methods of microstructural, magnetic, and dilatometric analyses (under isothermal conditions and with continuous cooling). The character of the structural components was studied, and the microhardness of the decomposition products was measured. The influence of the character of the structure on the thermal stability of the steel was also investigated. The presence of two stages of the decomposition of A, separated

Card 1/2

L 19305-63

ACCESSION NR: AR3006904

by a temperature interval of relative stability of A, was established. The relatively low C content and the character of the alloying of the steel are responsible for the unique mechanism of the decomposition of A according to the first degree type (temperature range 820-625C): the mechanism of decomposition of A into a ferrite-carbide mixture not eutectoidally, but by the formation of supersaturated ferrite, followed by the deposition of carbides from it, proved kinetically more favorable. Rates of cooling 1250 deg/hr are required to suppress the decomposition of A according to the first degree type. Decomposition of A according to a second degree type begins at 465C and reaches a maximum completeness at 300C (degree of conversion 89%). Increasing the temperature of austenitization from 960 to 1020C somewhat increases the stability of A in the first degree temperature region and exerts no noticeable influence on the kinetics of the conversion at the second degree temperatures. Steel with an initial structure of supersaturated ferrite possesses a minimum creep resistance; steel with a bainite initial structure possesses a maximum. The thermal stability of steel with a mixed structure can be extremely varied, depending on the quantitative ratio and mutual arrangement of the products of the first and second-degree decomposition of A. A. Nefedov.

DATE ACQ: 12Aug 63

SUB CODE: ML

ENCL: 00

Card 2/2

36597

S/126/62/013/003/009/023  
EO91/E135

18.451  
AUTHORS:

Syreyschikova, V.I., Levitin, V.V., and  
Farafonov, V.K.

TITLE:

On the influence of grain size of austenitic steels  
on their refractoriness and nature of fracture in  
creep

PERIODICAL: Fizika metallov i metallovedeniye, v.13, no.3,  
1962, 394-398

TEXT:

The influence of grain size and the properties of  
grains of varying dimensions in forgings of steel 3W612 K  
(EI612K), with respect to refractoriness and nature of cracks at  
650 and 700 °C was studied. The chemical composition of this  
steel (in %) is as follows: 0.09 C; 0.34 Si; 1.19 Mn;  
15.0 Cr; 36.5 Ni; 1.5 Ti; 3.2 W; 4.1 Co; 0.012 B; 0.013 P;  
0.004 S. An ingot 2.1 tons in weight was forged into a rod of  
300 mm diameter. The forging was cut into longitudinal templets  
of 20 mm thickness. Specimen billets were cut from peripheral  
portions of the latter, in order to exclude the influence of

Card 1/ 5

X

On the influence of grain size ... S/126/62/013/003/009/023  
E091/E135

defects in the central zone. The templets were soaked at 1200 °C for 2 hours and quenched. They were then ground on two opposite sides and etched in order to expose the nature and size distribution of the grains. Etching was carried out at room temperature in a solution consisting of a mixture of 20 weight parts of hydrochloric, 10 parts of nitric acid, and one part of potassium dichromate. The average grain size on the surface of billets of 20 x 20 mm cross section was determined by measuring the diameter of 200 grains. Selected billets were tempered in three stages: at 850 °C for 10 hours; at 700 °C for 20 hours; and at 650 °C for 30 hours. For the purpose of testing for refractoriness, specimens of 10 mm diameter and 100 mm working length were cut from the billets. The tests were carried out at 700 °C at loads of 22 and 18 kg/mm<sup>2</sup>, and at 650 °C at loads of 30 and 26 kg/mm<sup>2</sup>. Four specimens with various grain characteristics were tested for each load. The surfaces of the specimens after failure and their fractures were studied both visually and with the aid of a binocular microscope. Sections for metallographic study were made in the axial plane of the specimens.

Card 2/5

On the influence of grain size ... S/126/62/013/003/009/023  
E091/E135

These were polished electrolytically and etched in a sulphuric-phosphoric-chromic electrolyte. It was found that creep occurs under the above conditions both by viscous flow along inter-crystalline boundaries and by slip within the grains. During deformation, internal cracks develop along intercrystalline boundaries in the specimens in a direction perpendicular to the applied load. Large grains lying in the path of cracks so as to oppose their propagation perpendicular to the specimen axis, temporarily retard their spreading. No strengthening occurs, however, since failure develops further due to the formation of intercrystalline cracks in other places. The large grains, having stopped propagation of the cracks, are stress-relieved by slip, probably after they have rotated somewhat into a more favourable position. Vacancies accumulate along the slip planes, cracks form and cleavage occurs. Under the conditions investigated, failure occurs along the most closely packed planes of the type (111). The nature of failure (intra- or inter-crystalline) is determined essentially by the grain size in the specimen cross-section. As the grain size increases, the

Card 3/5

On the influence of grain size ...

S/126/62/013/003/009/023  
E091/E135

development of intercrystalline cracks becomes more difficult and the destruction acquires an intracrystalline character. So long as the grain size is small as compared with the diameter of the specimen, the stability of the latter does not decrease. In specimens, the cross section of which contain large grains (3-5 mm) comparable with the diameter of the specimen, cleavage in the large grains drastically weakens the cross section, as a result of which the specimen fails quite rapidly. Regions containing small, as well as large, grains exhibit different plastic properties, owing to localised predomination of different mechanisms of deformation. These result in the appearance of deflecting loads at the boundaries between these regions, which decrease the stability. There are 4 figures and 2 tables.

Card 4/5

On the influence of grain size ... S/126/62/013/003/009/023  
E091/E135

ASSOCIATION: Ural'skiy nauchno-issledovatel'skiy institut  
chernykh metallov  
(Ural Scientific Research Institute of Ferrous  
Metals)  
Institut tyazhelogo mashinostroyeniya pri UZTM  
(Institute of Heavy Machinery at UZTM)

SUBMITTED: Initially, June 5, 1961, and  
after revision, July 10, 1961.

Card 5/5

SYREYSHCHIKOVA, V.I.; LEVITIN, V.V.; FARAFONOV, V.K.

Investigating processes of hardening, creep, and rupture of austenitic steel. Issl. po zharoproch. splav. 10:116-123 '63. (MIRA 17:2)

SHEYNBERG, M.M.; FARAFONOV, V.K.; OVDINA, N.K.

Effect of tungsten, molybdenum, and vanadium on the recovery  
of chromium-nickel austenite. Fiz. met. i metalloved. 15 no.2:  
229-233 P '63. (MIRA 16:4)

1. Ural'skiy politekhnicheskii institut imeni S.M. Kirova.  
(Chromium-nickel steel—Metallurgy)

I. 53693-65 FWT(M)/EWP(w)/EPF(n)-2/EWA(d)/EPR/T/EWP(t)/EWP(z)/EWP(b)/  
EWA(c) Fad/Ps-4/Pu-4 IJP(c) JD/HW/JG

ACCESSION NR: AP5008787

S/0126/65/019/003/0411/0417  
539.292; 548. 53

4/8  
1/6  
B

AUTHOR: Shteynberg, M. M.; Farafonov, V. K.; Tret'yakova, E. G.; Mirzoyev, D. A.

TITLE: Effect of alloying on the softening and heat resistance of chromium-nickel austenite

SOURCE: Fizika metallov i metallovedeniye, v. 19, no. 3, 1965, 411-417

TOPIC TAGS: austenite, refractory, chromium alloy, nickel alloy

ABSTRACT: Various alloying elements are studied with regard to their effect on the heat resistance of austenite to determine an optimal composition for austenite steels. The material investigated was a chromium-nickel austenite for which the content of nickel and chromium (12.5-13% Ni; 14.5-15.5% Cr; 0.07-0.08% C) was selected so that quenched alloys with aluminum, molybdenum, tungsten, vanadium, titanium, niobium, and silicon in quantities from 1.5 to 3.5% would retain a purely austenitic structure. It is assumed that when a chromium-nickel austenite is alloyed with molybdenum, tungsten, niobium, and titanium, its heat resistance should increase. The heat resistance should also increase with the concentration of these

Card 1/2

L 53693-65

ACCESSION NR: AP5008787

1

elements in approximate conformity with the rate of retardation in the softening process and increase in the threshold of recrystallization. Silicon and aluminum have no effect on either of these factors and hence would not increase the heat resistance of a chromium-nickel austenite. The particular effectiveness shown by small additions of niobium and titanium is tied in with the state of the carbide phase and also with the possibility of an interaction of these elements with packing imperfections. Orig. art. has: 4 figures, 3 tables.

ASSOCIATION: Ural'skiy politekhnicheskiy institut (Ural Polytechnic Institute);  
NIITYaZhMASH UZTM

SUBMITTED: 30Sep63

ENCL: 00

SUB CODE: MM

NO REF SOV: 003

OTHER: 001

Card 2/2

L 49452-65 EPF(n)-2/EPR/EWA(c)/ENT(m)/EWP(b)/T/EWP(t) Ps-4/Pu-4 IJP(c) JW/  
 ACCESSION NR: AP5010988 JD/JG UR/0148/65/000/004/0164/0168

AUTHOR: Farafonov, V. K.; Shteynberg, M. M.; Olasov, V. N.

TITLE: Effect of titanium, niobium, silicon and aluminum on the softening of chromium-nickel austenite

SOURCE: IVUZ. Chernaya metallurgiya, no. 4, 1965, 164-168

TOPIC TAGS: austenitic steel, heat treatment, recrystallization

ABSTRACT: To facilitate the selection of optimal austenitic steel composition, a dozen samples containing relatively low amounts of the alloying elements--titanium, niobium, silicon and aluminum--were tested for softening, recrystallization threshold and activation energy of recrystallization. Samples were water-quenched from four temperatures from 1000 to 1150°C, with different holding times at each temperature, and subjected to cold working and "thermal" deformation with reductions from 20% to over 80%. Hardness tests of quenched alloys revealed only slight differences with respect to the concentrations of alloying elements used. Titanium and niobium, the latter even at a concentration of only 0.16%, very effectively inhibit the softening of chromium-nickel austenitic steel, increase the recrystallization threshold and activation energy of this process, and also inhibit grain growth at elevat-

Card 1/2

L 49452-65

ACCESSION NR: AP5010988

4

ed temperatures. With Titanium, an appreciable increase in the recrystallization threshold and inhibition of the softening process begins only at concentrations of about 0.4%. Silicon and aluminum have no significant effect on these processes. The role of  $\alpha$ -phase transformations is also taken into account. Further tests are needed to determine the effect of carbon in these alloys. Orig. art. has: 6 figures, 1 table 27

ASSOCIATION: Ural'skiy politekhnicheskiy institut (Ural polytechnical Institute)

SUBMITTED: 25May64

ENCL: 00

SUB CODE: MH

NO REF SOV: 004

OTHER: 000

Card 2/2 CC

SOV/124-58-10-11815

Translation from: Referativnyy zhurnal, Mekhanika, 1958, Nr 10, p 150 (USSR)

AUTHOR: Farafonov, Ye. S.

TITLE: Contribution to the Problem of the Investigation of the Mounting Stresses of Rolling-stock Roller Bearings (K voprosu issledovaniya talochnoy posadki vagonnykh rolikovykh podshpnikov)

PERIODICAL: Sh. rauchn. tr. Tashkentsk. inst. inzh. zh. d. transp., 1957  
Nr 7, pp 143-162

ABSTRACT: Determination of the stresses at the bearing pin of rolling stock axles resulting from vertical and longitudinal loads. A relationship is established between the stresses in the pin and the force exerted in making the press fit; it is concluded that consideration must be given to the press-fitting stresses in the design calculation of an axle. The results of an experimental investigation are presented.

L. I. Kiselev

Card 1/1

FARAFONOV, Ye. S.: Master Tech Sci (diss) -- "The problem of investigating the liners for freight-car roller bearings". Moscow, 1958. (Min Transportation USSR, All-Union Sci Res Inst of Railroad Transport), 120 copien (KI, No 3, 1959, 111)



**FARAFONOV, G. E.**

Durable grates for polymerization works. E. E. Farafonov and V. G. Makh. *Lutecia Delo* 9, No. 4, 18-21(1939); *Chem. Zentr.* 1939, I, 1240.—Of all the alloys investigated, the high-Cr cast alloys contg. C 3.1-3.21, Cr 30.7-31.37, Si 1.67-1.22 and Mn 1.14-0.63% had the longest life when used for such grates.  
M. G. Moore

ASB-SLA METALLURGICAL LITERATURE CLASSIFICATION

PARAFONOV, E. E.

PROCESSES AND PROPERTIES INDEX

9

The effect of chromium, nickel and molybdenum on the depth and the hardness of the external hardened layer of cast iron. E. E. Parafonov, I. S. Dukhin and V. A. Kuzin. *Litendo-Data-Me*, No. 4, 21-4(1939); *Chem. Zvesti*, 1940, 1, 121.—Increasing the amt. of Ni in cast iron which has a high total-C content reduces the depth of both the hardened layer and the transition layer. This reduction in depth is especially marked at a Ni content of 2%. If the C content in the hardened layer is increased, the depth of the hardened layer is gradually reduced. For the production of castings having an external hardened layer with both the true hardened zone and the transition zone of slight depth and with the middle gray zone of good mech. properties, Ni should be used as an alloying constituent. When the amt. of Cr in cast iron of high C content is increased, the depths of the hardened and the transition zones are increased. The addn. of Cr increases the brittleness of the middle gray zone of the cast iron. In cast iron having a high C content a Mo content of up to 0.14% decreases the depth of the hardened zone and especially that of the transition zone. Further increase in the Mo content up to 0.24% does not produce any essential improvement. For a cast iron of low C content a Mo content of up to 0.21% is without any essential influence; only after the Mo content has reached 0.40% is there a slight increase in the depth of the hardened zone and an essential increase in that of the transition zone.

M. G. Moore

ASM-A-4 METALLURGICAL LITERATURE CLASSIFICATION

FROM SYNOPTIC COLLECTION

SYNOPTIC COLLECTION

USSR/Solid State Physics - Mechanical Properties of Crystals and Polycrystalline  
Compounds, E-9

Abst Journal: Referat Zhur - Fizika, No 12, 1956, 34885

Author: Parafonov, Ye. Ye., Bobro, Yu. G.

Institution: None

Title: Heat-Resisting and Growth-Stable High-Strength Cast Iron with  
Spheroidal Graphite

Original

Periodical: Tr. Khar'kovsk. politekhn. in-ta, 1954, 5, 67-74

Abstract: See Referat Zhur - Khim, 1956, 30864

Card 1/1

F.H.H.F. ONOV, E.E.

5  
1-4E2C

11915\* (Russian.) Effect of Superheat Temperature and Magnesium Introduction on Properties of Cast Iron With Nodular Graphite. Villianle temperatury peregreva i vveda magalia na svoistva chuguna s sharovidnym grafitom. E. E. Furfonyov and M. S. Kolmakova. Litcinoe Proizvodstvo, no. 3, Mar. 1957, p. 14-16.

Mar. 1957, p. 14-16.  
Investigation of the relation between the amount of added Mg,  
the temperature of the ladle, and smelting variables.

fra RG and

137-58-3-5934

Translation from: Referativnyy zhurnal, Metallurgiya, 1958, Nr 3, p 211 (USSR)

AUTHORS: Farafonov, Ye. Ye., Gorushkina, L. P.

TITLE: Improving the Physico-mechanical Properties of Spheroidized Cast Iron by Means of Alloying with Nickel, Nickel-chromium, and Nickel-chromium-molibdenum (Povysheniye fiziko-mekhanicheskikh svoystv chuguna s sharovidnym grafitom putem legirovaniya nikelem, nikelem i khromom, nikelem, khromom i molibdenom)

PERIODICAL: Tr. Khar'kovsk. politekhn.in-ta, 1957, Vol 9, Nr 1, pp 17-28

ABSTRACT: An examination of the effect of single and complex additives, consisting of Ni, Mo, and Cr, on the improvement of the base metal and the physico-mechanical properties of spheroidized cast iron (SCI). Investigations were conducted on a SCI of the SPG-11-45 type with 0.5 percent-0.7 percent-0.9 percent-1.1 percent and 2.0 percent additions of Ni. It is established that optimum distribution of structural constituents and best ratio of strength and plastic characteristics of cast iron is achieved by concurrent addition of Ni, on the order of 1.0 percent, and of

Card 1/3

137-58-3-5934

Improving the Physico-mechanical Properties (cont.)

0.06 percent of Mg; the improvement in mechanical properties is attributable to the strengthening of the ferrite caused by the formation of a solid solution and by the sorbitization of its structure; the machinability of the cast iron is not impaired, however. It is noted that wear-resistance indices increase also. The authors stress the favorable effect of the addition of 1.0 percent of Ni which reduces quasi-isotropy almost to zero. When added in amounts exceeding 1.0 percent, the Ni in conjunction with Si has merely a graphitizing effect and lowers the mechanical properties of cast iron. In case of combined alloying of cast iron with Ni and Cr the  $\sigma_b$  increases by 14 percent on the average, while the  $\sigma_{b \text{ compr.}}$ , the  $a_k$ , and the deflection increase by 13 percent,

20 percent, and 17 percent, respectively; the  $\delta$  attains a 4 percent value. In the case of concurrent alloying with Ni and Mo the  $\sigma_b$  increases by 14-17 percent on the average, while the  $a_k$  increases by 25-30 percent. In combined alloying with Cr and Ni, as well as with Cr, Ni, and Mo, high values of  $E_{\text{tens.}}$  and  $E_{\text{compr.}}$  were obtained (on the order of  $1.6 \times 10^6$  to  $1.83 \times 10^6$  and  $1.6 \times 10^6$  to  $1.9 \times 10^6$ , respectively). A proper selection of alloying elements refines the precipitation of the spheroidal graphite somewhat, in connection with which certain improvements in mechanical properties, particularly of  $E$ , are observed. Owing to the combined alloying the field of application of SCI Card 2/3

137-58-3-5934

Improving the Physico-mechanical Properties (cont.)

as a substitute for components made of steel, non-ferrous metals, and alloys,  
may be widened even more to reduce the weight of structures below current  
levels.

S. Sh.

Card 3/3

S/128/60/000/007/014/0:7/XX  
A105/A033

AUTHORS: Parafonov, Ye.Ye., and Gorushkina, L.P.

TITLE: Alloying of Nodular Cast Iron

PERIODICAL: Liteynoye proizvodstvo, 1960, No. 7, pp. 24-26

TEXT: Tests of the physical and mechanical properties of nodular cast iron alloyed with copper, chromium, nickel and molybdenum are described. Chemical composition and structure of inspected cast irons are shown in Table 1 and their mechanical properties in Table 2. The influence of copper on the wear resistance of nodular cast iron was tested on a MW(MI) device by the friction method at a pressure of 100 and 150 kg/sq cm on 30XГСА (30KhGSA) steel brace hardened to 57.5. The abrasion coefficient was determined by weighing the specimens and the gage brace at intervals between 1,000-75,000 revolutions. The Curve 1 in Fig.2 corresponds to Ч 12-28 (Sch 12-28) cast iron; Curve 2 to БЧ 45-1.5 (VCh 45-1.5) cast iron without copper and Curve 3 to БЧ 45-1.5 (VCh 45-1.5) cast iron with copper. It was established that even small quantities of copper increase the wear resistance of nodular cast iron. ✓

Card 1/5

# Alloying of Nodular Cast Iron

S/128/60/000/007/014/017/XX  
A105/A033

The addition of copper to the cast iron led to a negligible decrease in shrinkage from 1.4 to 1.3%. After the usual annealing for 4 hours at 850°C, cooling down to 200°C and subsequent air cooling the nodular cast iron had a mainly ferritic structure with small quantities of undecomposed pearlite. The mechanical properties after annealing are shown in Table 3. The alloying elements and their quantities were determined according to recommendations in respect of gray cast iron with laminated graphite and also on account of previous tests on nodular iron. A characteristic of complex alloyed cast iron is the considerable crushing of pearlite. Complex alloying increases the tensile strength, especially if copper, nickel or molybdenum are used. The elasticity increases to  $1.6-1.7 \cdot 10^6$  in case of copper and chromium and to  $1.7-1.8 \cdot 10^6$  kg/sq cm in case of copper, nickel and molybdenum, as compared to  $0.6-0.8 \cdot 10^6$  of grey iron and  $1.1-1.2 \cdot 10^6$  of non-alloyed nodular cast iron. The shrinkage of nodular cast iron alloyed with copper and chromium was higher (1.5%) than that of non-alloyed nodular cast iron (1.4%). Alloying with nickel, molybdenum and copper reduced the shrinkage to 1.3-1.35%. Alloying with copper and chromium decreased the flowability of the metal, while alloying with copper, nickel and molybdenum did not affect it at all. There are 5 tables and 2 figures.

Card 2/5

S/128/60/000/007/014/017/XX  
A105/A033

Alloying of Nodular Cast Iron

Table 1:

1) No. of heat; 2) Chemical composition; 3) Structure; 4) Prior to pickling; 5) After pickling; 6) Coarse graphite flakes; 7) Finely whirled graphite; 8) Spheroidal graphite; 9) Spheroidal graphite; 10) Medium-size spheroidal graphite; 11) Mixed spheroidal graphite; 12) Coarse-laminated pearlite, small ferrite section; 13) Laminated pearlite, small ferrite parts; 14) Laminated pearlite, ferrite fringes around graphite; 15) Fine-laminated pearlite, fine ferrite fringes around graphite; 16) Laminated pearlite, now and then ferrite fringes; 17) Fine-laminated pearlite, insignificant ferrite parts.

Таблица 1

№ плавки	2) Химический состав в %								3) Структура	
	C <sub>об</sub>	C <sub>Fe</sub>	Si	Mn	P	S	Mg	Cu	4) до травления	5) после травления
1	3,41	1,11	2,25	0,6	0,12	0,05	—	—	Грубые пластинки графита	Грубопластинчатый перлит, небольшие участки феррита
2	3,47	0,99	2,48	0,69	0,12	0,05	—	0,95	Мелкий завыренный графит	Пластинчатый перлит, небольшие участки феррита
3	3,42	0,90	2,80	0,6	0,14	0,016	0,06	—	Шаровидный графит	Пластинчатый перлит, оторочки феррита вокруг графита
4	3,33	1,18	2,74	0,51	0,15	0,012	0,06	0,6	Шаровидный графит	Тонкопластинчатый перлит, тонкие оторочки феррита вокруг графита
5	3,40	0,90	2,48	0,42	0,13	0,014	0,07	0,91	Шаровидный графит, средний	Пластинчатый перлит, изредка феррит в виде оторочек
6	3,44	1,19	2,86	0,52	0,15	0,012	0,04	1,06	Смешанный шаровидный графит	Тонкопластинчатый перлит, небольшие участки феррита

Card 3/5

Alloying of Nodular Cast Iron

S/128/60/000/007/014/017/XX  
A105/A033

Table 2

Таблица 2

1) № плавки	2) Механические свойства					HB
	$\sigma_{0.2}$ в кг/мм <sup>2</sup>	$\delta$ в мм	$\sigma_B$ в кг/мм <sup>2</sup>	$\sigma_{сж}$ в кг/мм <sup>2</sup>	$\sigma_{\lambda}$ в кг/мм <sup>2</sup>	
1	28,4	4,8	12,7	80,8	—	149
2	39,8	2,8	17,2	88,0	—	256
3	92	3,8	48,3	188,0	0,16	302
4	97,0	2,4	87,2	174	0,63	286
5	104,6	2,9	81,4	193	0,43	278
6	87,6	2,4	61,0	172	0,38	321

3) \* Данные испытания образцов 10x10 мм с надрезом.

- 1) No. of heat
- 2) Mechanical properties
- 3) Test data from notched 10 x 10 mm specimens

Card 4/5

Alloying of Nodular Cast Iron


S/128/60/000/007/014/017/XX  
A105/A033

Table 3

Таблица 3

Cu %	Mg %	$\sigma_{0.2}$ кг/мм <sup>2</sup>	$\delta$ мм	$\sigma_{0.2}$ кг/мм <sup>2</sup>	$\delta$ мм	$\sigma_{0.2}$ кг/мм <sup>2</sup>	$\delta$ мм	$\sigma_{0.2}$ кг/мм <sup>2</sup>	HB
—	0,04	92,0	3,5	45,3	0,6	103	—	0,45	302
—	0,06	91,5	15	40,5	5,5	254	64	1,37	155
0,91	0,07	104,6	2,9	51,4	1,0	193	—	0,43	277
0,99	0,04	103,2	14	50,5	11	245	60	2,0	155

Figure 2



No. of revolutions

Card 5/5

2. THEORY , 1. UNITED STATES ,

dissertation: "An investigation of the milk pasteurizer for cattle-breeding farms."  
 Cand. Ag. Sci., Joint Scientific Council of the All-Union Sci. Res. Institute for the  
 Mechanization of Agriculture (VIM) and the All-Union Sci. Res. Institute for the Elec-  
 trification of Agriculture (VIEKhA), 22 Jun 54. (Voenarmyaya Moskva, Moscow,  
 11 Jun 54)

DD: 304 13, 23 Dec 1954

KOROLEV, V.F., kand.tekhn.nauk; PARAFONOVA, N.I., kand.tekhn.nauk

Principles for the parameters of milking machines. Nauch. trudy  
VINSKH 4:88-112 '59. (MIRA 13:11)

(Milking machines)

CHAKABAYEV, S.Ye.; IMASHEV, N.U.; TOKAREV, V.P.; KONONOV, Yu.S.; KORSUN, P.Ye.;  
VOTSALEVSKIY, E.S.; IVANOV, V.A.; PARAFONOVA, N.V.; SHAKHOVOY, A.I.

Uzen' gas and oil field; outline of geology and oil and gas potentials.  
Izv. AN Kazakh. SSR. Ser. geol. 21 no.4:16-30 J1-Ag '64. (MIRA 17:11)

1. Institut geologii i geofiziki, Gur'yev.

FARAFONT'YEVVA, A.A.

X-ray picture of pulmonary actinomycosis [with summary in English].  
Vest.rent. 1 rad. 32 no.6:37-42 N-D '57. (MIRA 11:3)

1. Iz rentgenovskogo otdeleniya (zav. N.K.Simagina, nauchn.rukovod.-  
prof. K.E.Abarbanel') Klinicheskoy bol'nitsy No.6 (glavnyy vrach  
N.S.Shevyakov).

(ACTINOMYCOSIS, diag.

lungs, x-ray diag. (Rus)

(LUNG DISEASES, diagnosis,

actinomycosis, x-ray (Rus)

COUNTRY	: GDR	E-2
CATEGORY	: Analytical Chemistry- Analysis of Inorganic Substances.	
ABS. JOUR.	: RZKhim., No. 16 1959, No.	56860.
AUTHOR	: Korkisch, J. and Farag, A.	
INST.	: Not given	
TITLE	: On the Analytic Chemistry of Zirconium. II. The Concentration of Zirconium as the Negatively Charged Sulfate Complex on Strongly Basic*	
ORIG. PUB.	: Z analyt Chem, 166, No 2, 81-88; No 3, 170-180, 181-185 (1959)	
ABSTRACT	: II. A concentration method is described, based on the sorption of Zr as the negatively charged	
	*Amberlite IRA-400 Exchange Resins and Separation of Zirconium from Thorium, Titanium, Iron, Aluminum, and Many Other Elements. III. A New Method for the Concentration of Zirconium on Strongly Basic Anion Exchange Resins and Its Application to the Determination of Zirconium in Silicate Rocks. IV. On the Sorption of the Zirconium Ascorbate on Strongly Basic Anion Exchange Resins.	

CARD: 1/8

COUNTRY : GDR E-2  
CATEGORY :  
AB3. JOUR. : RZKhim., No. 16 1959, No. 56860  
AUTHOR :  
INST. :  
TITLE :  
ORIG. PUB. :  
ABSTRACT : sulfate complex on the H-form (sulfuric acid)  
of Amberlite IRA-400 exchange resin with sub-  
sequent elution of the Zr with HCl solution.  
The column is packed with the above-indicated  
anion exchange resin (grain size 0.1-0.3 mm)  
and washed successively with a 4 N solution of  
H<sub>2</sub>SO<sub>4</sub>, water, and an H<sub>2</sub>SO<sub>4</sub> solution of the same  
concentration as the solution to be analyzed  
(based on H<sub>2</sub>SO<sub>4</sub>). The unknown solution, contain-  
ing 400 gammae of Zr in 100 ml, is passed through

CARD: 2/18

83

COUNTRY	:	GDR	E-2
CATEGORY	:		
ABS. JOUR.	:	RZKhim., No. 16 1959, No.	56860
AUTHOR	:		
INST.	:		
TITLE	:		
ORIG. PUB.	:		
ABSTRACT	:	<p>the column at the rate of 0.5 ml/min; the column is washed with a solution of <math>H_2SO_4</math> of the same concentration as the unknown solution in <math>H_2SO_4</math> and the Zr is extracted with 4 N HCl solution. 0.05-0.2 N <math>H_2SO_4</math> solutions result in quantitative sorption of Zr; a further increase in the concentration of the <math>H_2SO_4</math> leads to a sharp decrease in the sorption of Zr; the latter passes through the column practically unadsorbed in an 8 N <math>H_2SO_4</math> solution. 10 mg of Zr are ad-</p>	

CARD: 3/18

COUNTRY	:	GDR	E-2
CATEGORY	:		
ABS. JOUR.	:	RZKhim., No. 16 1959, No.	56860
AUTHOR	:		
INST.	:		
TITLE	:		
ORIG. PUB.	:		
ABSTRACT	:	<p>sorbed from a 0.1 N <math>H_2SO_4</math> solution prior to breakthrough; the adsorbed Zr is quantitatively extracted on passing 100 ml 4 N HCl solution through the column. The addition of <math>Na_2SO_4</math> or NaF does not affect the breakthrough capacity of the resin. The addition of large amounts of <math>(NH_4)_2SO_4</math> (over 10 gms per 100 ml of unknown solution) results in a nonquantitative adsorption of Zr. The adsorption of Zr is even more markedly decreased by the presence of <math>Cl^-</math> and <math>NO_3^-</math>.</p>	

CARD: 4/18

84

COUNTRY : GDR  
CATEGORY :

E-2

ABS. JOUR. : RZKhim., No. 16 1959, No.

56360

AUTHOR :  
INST. :  
TITLE :

ORIG. PUB. :

ABSTRACT : Quantitative sorption of Zr is observed only at NaCl concentrations of  $< 2.5$  gms/liter and  $\text{NaNO}_3$  concentrations of  $< 1$  gm/liter of unknown solution, 0.1 N in  $\text{H}_2\text{SO}_4$ . The above-described method can be applied to the separation of Zr from all elements, in addition to Sn, V, Mo, W, and U, which are also adsorbed on the above-indicated anion-exchange resin and completely or partially eluted with HCl. Of the last-enumerated elements only Mo and W interfere

CARD: 5/18

COUNTRY	:	GDR	E-2
CATEGORY	:		
ABS. JOUR.	:	RZKhim., No. 16 1959, No.	55860
AUTHOR	:		
INST.	:		
TITLE	:		
ORIG. PUB.	:		
ABSTRACT	:	<p>with the complexometric titration of <math>\text{H}_2\text{SO}_4</math> with Solochrome Violet R. Even small amounts of <math>\text{PO}_4^{3-}</math> produced by the precipitation of Zr phosphate, make impossible the ion exchange filtration of the unknown solution. The method has been applied successfully to the separation of Zr from Mg, Ca, Al, Cu(2+), Zn, Cd, Ti(4+), Th(4+), Cr(3+), Mn(2+), Fe(3+), Co, Ni, and the rare earth elements; the starting unknown solution in each case contained 0.1 gm-equiv per liter of <math>\text{H}_2\text{SO}_4</math>.</p>	

CARD: 6/18

85

COUNTRY	:	GDR	E-2
CATEGORY	:		
ABS. JOUR.	:	AZKhim., No. 16 1959, No.	56860
AUTHOR	:		
INST.	:		
TITLE	:		
ORIG. PUB.	:		
ABSTRACT	:	III. A finely ground sample of ore to be analyzed is mixed with a 6-10-fold excess of anhydrous $\text{Na}_2\text{CO}_3$ and heated in a covered Pt crucible, first at low temperatures, later at 1,000-1,200°; the melt is leached with water over a water bath and filtered, giving a transparent filtrate. The precipitate containing Zr, Fe, Ti, Be, Ni, Co, Zn, Mg, the rare earth elements, and the alkaline earth elements as well as most of the Th and Al, is washed on the filter with a 1%	
CARD:		7/18	

COUNTRY	: UDR	
CATEGORY	:	
ABS. JOUR.	: RZKhim., No. 16 1959, No.	56860
AUTHOR	:	
INST.	:	
TITLE	:	
PUB.	:	
ABSTRACT	: solution of $\text{Na}_2\text{CO}_3$ and dissolved in HF which has been used in the rinsing of the Pt crucible. The solution obtained is treated with 100-450 mg Al as $\text{AlCl}_3$ (for the elimination of Zr co-precipitation by the precipitating fluorides of the rare earths and alkaline earths in the absence of Al, the $\text{CaF}_2$ is extracted from the liquid phase up to 98% Zr [sic]; coprecipitation is eliminated when the Al : Ca ratio exceeds 1), evaporated to dryness, an excess of HF is added, and the evapora-	
CARD:	8/18	
86		

COUNTRY : GDR  
CATEGORY :

E-2

ABS. JOUR. : RZKhim., No. 16 1959, No.

56860

AUTHOR :  
INST. :  
TITLE :

ORIG. PUB. :

ABSTRACT : tion is repeated. The dry residue is treated with 100 ml 0.1 N  $H_2SO_4$  containing 0.5 gm NaF with heating, the solution is left to stand 10-12 hrs, the precipitate of rare earth and alkaline earth element fluorides is filtered, and washed with 0.1 N  $H_2SO_4$ . The filtrate containing Ti, Fe, Al, Zr, Be, Co, and Zn is passed through the anion exchange column at the rate of 0.5 ml/min; before the separation, the column is washed successively with 1.N HCl solution, water, 4 N

CARD: 9/18

COUNTRY	: GDR	E-2
CATEGORY	:	
ABS. JOUR.	: RZKhim., No. 16 1959, No.	56860
AUTHOR	:	
INST.	:	
TITLE	:	
ORIG. PUB.	:	
ABSTRACT	: H <sub>2</sub> SO <sub>4</sub> , water, and 0.1 N H <sub>2</sub> SO <sub>4</sub> . Following passage of the unknown solution through the column, the latter is washed with 0.1 N H <sub>2</sub> SO <sub>4</sub> (30 ml), after which the Ti is eluted from the column, using a mixture of 50 ml 0.1 N H <sub>2</sub> SO <sub>4</sub> and 5 ml perhydrol. For best results the eluent solution should be passed through the column countercurrent to the unknown solution. When a colorless filtrate appears, the column is washed with 0.1 N H <sub>2</sub> SO <sub>4</sub> (50-100 ml) and the Zr is eluted by passing	
CARD:	10/18	

87

COUNTRY : GDR  
CATEGORY :

E-2

ABS. JOUR. : RZKhim., No. 16 1959, No.

56860

AUTHOR :  
INST. :  
TITLE :

ORIG. PUB. :

ABSTRACT : 100 ml of 4 N HCl through the column. The Zr is determined complexometrically in the filtrate using Solochrome Violet R as indicator. The results obtained are in good agreement with those obtained from gravimetric analysis. Practically identical results are obtained from the determination of Zr in silicate drops using Amberlite IRA-400, Dowex-1, and Dowex-2 anion exchange resins. The method described can be applied to the separation of Zr from considerable

CARD: 11/18

COUNTRY : GDR  
CATEGORY :

E-2

ABS. JOUR. : RZKhim., No. 16 1959, No.

56860

AUTHOR :  
INST. :  
TITLE :

ORIG. PUB. :

ABSTRACT : excesses of  $H_3PO_4$ . In the latter case 100 ml of unknown solution, 0.1 N in  $H_2SO_4$ , are passed through the column which is subsequently washed with 0.1 N  $H_2SO_4$  (100 ml); the Zr is eluted from the rinsed column with 4 N HCl solution (100 ml). When the unknown solution contains Th, the precipitate of  $ThF_4$  is first filtered after which the filtrate is passed through the column. The Zr is eluted with 4 N HCl solution following rinsing of the column with 0.1 N  $H_2SO_4$ .

CARD: 12/18

88

COUNTRY : GDR  
CATEGORY :

E-2

ABS. JOUR. : RZKhim., No. 16 1959, No.

56860

AUTHOR :  
INST. :  
TITLE :

ORIG. PUB. :

ABSTRACT : In the presence of a 20-fold excess of Sn or Sb,  
the results from the determination of Zr are low  
and the method therefore cannot be applied to  
the analysis of Sn and Sb ores.

CARD: 13/18

COUNTRY : GDR  
CATEGORY :

E-2

ABS. JOUR. : RZKhim., No. 16 1959, No.

55560

AUTHOR :  
INST. :  
TITLE :

ORIG. PUB. :

ABSTRACT : IV. The anion exchange column used in the separation of Zr as the ascorbate complex is first rinsed with 1 N HCl solution, water, and 1 % ascorbic acid solution the pH of which has been adjusted to 4 by the addition of ammonia. The unknown solution is then passed through the column at the rate of 0.5 ml/min (pH 4, 2% in ascorbic acid). Following rinsing of the column with a 1% solution of ascorbic acid of pH 4 (30 ml) and water (30 ml), the Zr is eluted using 100 ml

CARD: 14/18

89

COUNTRY : GDR  
CATEGORY :

E-2

ABS. JOUR. : RZKhim., No. 16 1959, No.

56860

AUTHOR :  
INST. :  
TITLE :

ORIG. PUB. :

ABSTRACT : M. [?] HCl. Under the conditions indicated the operating exchange capacity of the columns packed with Amberlite IRA-400, Dowex-1, and Dowex-2 varies and constitutes 1.0, 1.5, and 2.0 mg Zr, respectively.  $\text{SO}_4^{2-}$ ,  $\text{Cl}^-$ , and especially  $\text{NO}_3^-$  can interfere with the qualitative adsorption of Zr. Qualitative adsorption of Zr is observed at Na salt concentrations in the unknown solution of  $\leq 3.0$  gms/liter ( $\text{Na}_2\text{SO}_4$ ),  $\leq 2.5$  gms/liter ( $\text{NaCl}$ ), or  $\leq 1.0$  gms/liter

CARD: 15/18

COUNTRY	: GDR	E-2
CATEGORY	:	
ABS. JCUR.	: RZKhim., No. 16 1959, No.	56860
AUTHOR	:	
INST.	:	
TITLE	:	
ORIG. PUB.	:	
ABSTRACT	: (NaNO <sub>2</sub> ). The quantitative elution of Zr requires the passage of 100 ml 1 N HCl through the column; 0.1 N HCl extracts 90% of the Zr and 0.1 N H <sub>2</sub> SO <sub>4</sub> fails to extract Zr. The quantitative determination of Zr in hydrochloric acid eluates is preceded by evaporation of the solutions over a water bath, treatment of the dry residue with conc HNO <sub>3</sub> , followed by repeated evaporation and treatment with HNO <sub>3</sub> with the addition of a small amount of water. The solution obtained is evapo-	

CARD: 16/18

90

COUNTRY : GDR  
CATEGORY :

56860

ABS. JOUR. : RZKhim., No. 16 1959, No.

AUTHOR :  
INST. :  
TITLE :

ORIG. PUB. :

ABSTRACT : rated to dryness in a Pt crucible, the residue is ignited, and the  $ZrO_2$  is dissolved with evaporation in a few ml of HF. The residue is dissolved in 10 ml 1 N HCl and titrated by the complexometric method. The method described can be applied to the concentration of Zr in various waters, as well as to the separation and quantitative determination of Zr in minerals following their fusion with soda and separation of silicic acid. The mineral to be analyzed must not con-

CARD: 17/18

COUNTRY : GDR  
CATEGORY :

ABS. JOUR. : RZhKhim., No. 16 1959, No.

56350

AUTHOR :  
INST. :  
TITLE :

ORIG. PUB. :

ABSTRACT : tain phosphates nor elements interfering with  
the determination of Zr (see preceding communi-  
cations). For Communication I see RZhKhim,  
No 13, 1959, 45539.

N. Polyanskiy

CARD: 18/18

91

HUNGARY

DENES, Geza, FARAGO, Anna; Medical University of Budapest, Institute of Medical Chemistry (Budapesti Orvostudományi Egyetem, Orvosi Vegytani Intézet).

"Properties of the Allosteric Enzymes of Arginine Biosynthesis in *Chlamydomonas Reinhardtii*."

Budapest, A Magyar Tudományos Akadémia Biológiai Tudományok Osztályának Közleményei, Vol VIII, No 2, 1965, pages 195-201.

**Abstract:** The characteristics of feed-back inhibition of enzymes in amino acid biosynthesis are described in general. These were demonstrated by specific experiments involving arginine biosynthesis in fresh-water algae, starting with acetylglutamic acid. The feed-back sensitive enzyme, acetylglutamic acid-gamma-phosphokinase, can be inhibited with arginine.  $Mg^{++}$  and ATP are needed for the reaction. To measure the enzyme activity, the reaction mixture was incubated in the presence of  $NH_2OH$  and the product was determined as a hydroxamic acid. The experiments were carried out with a 20-fold purified extract of the enzyme. The pH optimum of the catalytic action and inhibition of the enzyme, the similar but weaker action by arginine analogues are reported. By using urea in less than 1.5 M concentration, a reversible suspension of feed-back inhibition was achieved with intact enzyme activity. By the addition of more arginine, inhibition can be achieved  
1/2

- 4 -

HUNGARY

Budapest, A Magyar Tudományos Akadémia Biológiai Tudományok Osztályának Közleményei, Vol VIII, No 2, 1965, pages 195-201.

"APPROVED FOR RELEASE: 03/13/2001" CIA-RDP86-00513R000412420010-7

again. The arginine/urea ratio which produces a certain degree of inhibition was found to be constant. The seemingly competitive character of the urea function can be explained by several theories. These are discussed. The findings have indicated that the enzyme can exist in various native conformations representing different functional states among which inter-conversion is possible and necessary. Future experiments are planned to elucidate the precise details of change in conformation caused by the allosteric effect. All references are Western.

TURKI, A.R.; YUSSEF, Yu.L.; SALEM, T.M.; FARAG, M.S.; KHANAFI, Z.

Physical properties of yellow mercuric and red mercurous oxides.  
Dokl. AN SSSR 142 no.5:1095-1097 F '62. (MIRA 15:2)

1. Yegipetskiy natsional'nyy issledovatel'skiy tsentr, Kair,  
Ob'yedinennaya Arabskaya Respublika. 2. Inostranny chlen  
AN SSSR (for Turki).  
(Mercury oxide)

FARAGA, Tibor. dr. (Budapest, XI., Sztoczek u.2)

Nonzero domain of polynomials. Periodica polytechn electr  
8 no.1:101-114 '64.

1. Lehrstuhl für Mathematik, Technische Universität, Budapest.  
Vorgelegt von Prof. Dr. I. Fenyő.

FARAGO A., VARGO V. OLAH F. and FARUDIN E.

1st Dept. of Med., Univ. med. Sch., Szeged, Hungary. \*Contribution to the neurohormonal mechanism of gastric secretion ACTA MED. ACAD. SCIENT. HUNG. (Budapest) 1954, 5/1-2 (143-148) Graphs 31

In order to establish the importance of vagal activity in gastric secretion the authors studied the insulin-induced gastric secretion. In normal subjects the peak of HCl secretion comes 20 min. later than that of pepsin secretion. Gastrectomized subjects injected with insulin either do not secrete any HCl or fail to show a dissociation in the response. The pepsin production is unaltered. The authors ascribe this difference in behaviour to the action of an agent liberated by vagal stimulation from the distal part of the stomach. The secretory effect of this substance could be demonstrated in dogs, transfused with blood from hypoglycaemic donor dogs. The recipients showed an increased secretion of HCl while the pepsin secretion did not alter.

Szilard - Pecs (VI, 2)

SO: EXCERPTA MEDICA, Section II, Vol. 7, No. 11

FARAC, B.

Test track of the Budapest Underground Railway. p. 66. KOZLEKEDESTUDOMANYI  
SZEMLE. (Kozlekedesi Kiado) Budapest. Vol. 6, no. 2, Feb. 1956.

SOURCE: East European Accessions List (EEAL) Library of Congress  
Vol. 5, no. 8, August 1956

FARAGO, Bela

Some aspects of choosing radioactive isotopes applicable in the textile industry. Magy textil 14 no.12:529-536 D '62.

1. Magyar Gyapjufono es Szovogyar.

FARAGO, Bela, okleveles mernok

Ray absorption of threads and the theoretical foundations  
of isotopic hygrometry. Magy textil 15 no.12:545-548 D '63.

1. Magyar Gyapjufono es Szovogyar.

*FARAGO E.*

**FARKDIN, Imre, dr; NOVASZEL, Ferenc, dr; FARAGO, Endre; VARRO, Vince, dr.**

**Studies on pepsin in gastric contents, in urine and in blood.  
Magy beloryv. arkh. 7 no.3:70-76 June 54.**

**1. Szegedi Orvostudományi Egyetem I. sz. Belklinikája (igazgató:  
Hetenyi Géza dr.)**

**(PEPSINS,  
in blood, gastric contents, & urine)  
(BLOOD, (URINE,  
pepsin pepsin)  
(STOMACH,  
pepsin in gastric contents)**

*FARAGO E.*

NOVASZEL, Ferenc, dr; FARADIN, Imre; FARAGO, Endre; VARRO, Vince.

Gastric secretion and excretion of uropepsin in active and inactive phases of duodenal ulcer. *Magy belorv. arch.* 7 no.3:77-82 June 54.

1. Szegedi Orvostudományi Egyetem I. sz. Belgyógyászati Klinika-  
jának közleménye (igazgató :prof. dr Hetenyi Géza)  
(PEPTIC ULCER, metabolism in,  
uropepsin secretion)  
(PEPSINS,  
secretion in peptic ulcer)

FARAGO, Endre, dr.

Therapeutic use of  $\alpha,\alpha'$ -diethyl-4,4'-stilbenediol dipropionate  
and drugs with similar effects in primary congelations. *Borogygy.*  
vener. szemle 10 no.5:218-221 Sept 56.

(DIETHYLSTILBESTROL, related cpds.  
dipropionate, ther. in primary frostbite (Hun))  
(FROSTBITE, ther.  
diethylstilbestrol dipropionate in primary frostbite (Hun))

FARAGO, Endre

Cetyl pyridinium bromide in resistant cases of fungus diseases  
of the skin. Borgyogy. vener. szemle 11 no.4:148-150 Aug 57.

(ANTISEPTICS, QUATERNARY AMMONIUM, ther. use  
cetyl pyridinium bromide in resistant fungus dis.  
of skin (Hun))

(FUNGUS DISEASES, ther.  
skin, cetyl pyridinium bromide in resistant cases (Hun))

(SKIN DISEASES, ther.  
fungus dis., cetyl pyridinium bromide in resistant cases  
(Hun))

WEISZ, Pal; GLAZ, Edit; DEMECZKY, Mihalyne; FARAGO, Erika; LAX, Vera

Chromatographic determination of corticosterone in the peripheral  
blood of rats. Kiserletes Orvostud. 13 no.1:54-57 Mr '61.

1. Orszagos Reuma es Furdougyi Intezet Kutato Laboratoriuma es  
a Budapesti Orvostudomanyi Egyetem II. sz. Belklinika.  
(ADRENAL CORTEX HORMONES blood)

VARGA, Ferenc; FARAGO, Elza

Ternary constitutional diagrams for foundry sands. Koh lap 93 no.5:  
Suppl. Ontode 11 no.5:106-111 My '60.

1. Vasipari Kutato Intezet.

VARGA, Ferenc; V. FARAGO, Elza

Mechanization of core production. Koh lap 93 no.6:Suppl: Ontode 11  
no.6:126-132 J. '60.  
1. Vasipari Kutato Intezet.

FARAGO

"Determination of the oxygen, hydrogen and nitrogen contents of iron"  
by L.I. Levi. Reviewed by Farago. Koh lap 93 no.1; Suppl: Ontode 11  
no.1:23-24 Ja '60.

FARAGO, E.

Periodical reviews by E. Farago. Koh lap 93 no.2;Suppl: Ontode 11  
no.2:46-48 F '60.

FARAGO, Ferents [Farago, Ferenc], doktor (Budapesht)

Maintenance and repair of the rolling stock on Hungarian rail-  
roads. Zhel.dor.transp. 44 no.9:24-27 S '62. (MIRA 15:9)  
(Hungary--Railroads--Repair shops)

FARAGO, Ferenc, dr., okleveles mérnök

Railroad transportation of Holland and the Utrecht railroad  
museum. Vasut 12 no.8:22-23 25 Ag '62.

FERENC FARAGO  
HUNGARY/Chemical Technology. Chemical Products and Their Application.  
Food Industry. H-28

Abs Jour: Referat Zhur-Khimiya, No 5, 1958, 16092.

Author : Farago Ferenc, Szilagyi Istvan

Inst :

Title : Problems of Candied Fruit Manufacture.

Orig Pub: Elelm. ipar, 1957, 11, No 1, 16-20.

Abstract: No abstract.

Card : 1/1

PATAKY, Jozsef, dr.; DOMJAN, Lajos, dr.; LUSZTIG, Gabor, dr.; FARAGO, Ferenc,

APPROVED FOR RELEASE: 03/13/2001 CIA-RDP86-00513R000412420010-7

Serum protein changes in silicosis and in tuberculosis. Tuberkulozis  
15 no.7:215-217 JI '62.

1. Bacs-Kiskun Megyei Tanacs Korhaza II. Belosztalyanak, Tudosztalyanak,  
Prosecturajanak es Laboratoriumanak kozlemenye.  
(TUBERCULOSIS PULMONARY blood) (SILICOSIS blood)  
(BLOOD PROTEINS)

DEC ?

BENEDICT, Janos, dr.; HOMOKY, Istvan, dr.; FARAGO, Ferenc, vegyeszmernok

Observations on a patient with dermatomyositis, treated with anti-malarial drugs and anabolic hormones. Orv. hetil. 103 no.38:1793-1798 23 S '62.

1. Bacs-Kiskun Megyei Tanacs Korhaz (Kecskemet), I. Belosztaly.  
(DERMATOMYOSITIS) (HORTESTOSTERONE) (CHLOROQUINE)  
(URINATION DISORDERS)

FARAGO F.

M-2

HUNGARY/Cultivated Plants - Grains.

Abs Jour : Ref Zhur - Biol., No 7, 1958, 29735

Author : Farago, F., Laslo, D.

Inst : -

Title : The Time, Method and Means of Caring for Corn Planted in  
Two Rows in Godollo.

Orig Pub : Magyar mezogazd., 1957, 12, No 9, 5-6 (veng.).

Abstract : No abstract.

Card 1/1

FARAGO, Ferenc; SZILAGYI, Istvan

Theoretical and technological questions on the manufacture  
of candied fruits. Elelm ipar 11 no.1:16-20 Mr '57.

FARAGO, Ferenc, dr., okleveles mernok

Passenger car wash and the modernization of railorad vehicle  
repair. Vasut 14 no. 1: 32 Ja '64.

FARAGO, Ferenc, dr., okleveles mernok

Is it economical to convert wooden-framed passenger cars into  
iron-framed ones? Vasut 13 no.6:27 Je '63.

VURDELJA, Nemanja, prof. dr.; NIKOLIC, Vojislav; FARAGO, Franja;  
KAPAMADZIJA, Borislav.

A new antiepileptic drug. Med. pregl. 17 no.10:605-607 '64.

1. Klinika za neuropsihijatrijske bolesti Kliničko bolnice  
u Novom Sadu (Nacelnik: Prof. dr. Nemanja Vurdelja).

FARAGO, Gyula; KERÉKGYARTO, Pál

Technical and economic questions relating to the prime cost in fiber spinning mills. Magyar Textil 15 no.10:467-473 0 '63.

1. Lenfonó és Szövőipari Vállalat (for Farago). 2. Textilipari Kutató Intézet (for Kerekgyarto).

FARAGO, Gyorgy, dr.; WERMER, Tamas, dr.; LANYI, Marton, dr.

A case of double ureter complicated by megaloureter. Magy.  
sebesz. 16 no.6:397-400 D '63.

1. Az Orvostovábbképző Intézet (igazgató: Prof. Magyar Imre  
dr.) Urologia osztályának (főorvos: Farago György dr.) és  
Röntgen Tanszékének (főorvos: Prof. Deák Pál dr.) közleménye.  
(URETER) (ABNORMALITIES) (NEPHRECTOMY)  
(UROGRAPHY) (PATHOLOGY)

The image shows a single frame from a microfilm reel. The frame is rectangular with perforated edges, typical of microfilm. Inside the frame, there is a document page. At the top left of the document, there is a handwritten number "7". The main title of the document is "MAGYAR HIVERIAKADÉMIA— POWER BOOMONT IN HUNGARY Vol. III. - 1970. No. 7 - 12, July - Dec.". Below the title, there is a section heading "on Furgis" followed by "Condensers in refrigerating plants .... 113-116". On the right side of the document, there is a handwritten number "55". The bottom of the document features two sections: "BIBLIOGRAPHIC LITERATURE CLASSIFICATION" on the left and "CROSS REFERENCE INDEX" on the right. The entire document is centered within the microfilm frame.

212

212

421.483

10. Formation of ice in tube-type ice making equipment — *Jégipadák csőgyártó berendezésben* — by Gy. Faragó. (Power Economy in Hungary — *Magyar Energiagazdálkodás* — Vol. IV, No. 6, pp. 199—203, June 1951, 5 figs.)

The purpose of tube-type ice making equipment is the rapid production of ice — without the use of brine and which can easily be chopped — by means of inexpensive, light weight refrigerating apparatus. The equipment consists of a vertically arranged system of tubes surrounded by a jacket, circulating pumps for the refrigerant (usually ammonia) and the delivery of the water intended for freezing, the piping, and the equipment for chopping the ice. The refrigerant, trickling along the outer surface of the tubes, evaporates and cools the tube walls

which, in turn, freeze the water flowing down in thin streams inside the tubes. The advantage of the equipment is that it costs one third and requires one fifth of the space of the earlier equipment, and can be handled by one attendant. Sanitary requirements are also satisfied to a greater degree. The ice cylinders are loosened from the tubes by steam fed into the space between the jacket and the tubes. The cylinders dropping out of the tubes are cut to the required length by a rotary device and are finally discharged. Maximum ice production is obtained at a 5 min. freezing cycle and a constant evaporating temperature of  $10^{\circ}\text{C}$ .

FARAGÓ, Gy.

✓ 4284. Faragó, Gy., Improving the economy of the cooling cycle (*Hungarian Energy Abstracts* 5, 8, 212-214, Aug. 1952).

The economy of operation in refrigeration plants where cooling is applied at different temperatures can be increased by first cooling the coolant—to be charged into an evaporator at a lower temperature—in an evaporator at a higher temperature. Throttling losses are reduced in this way; vapors arising from the cooling of the coolant are sucked off by a compressor at a higher temperature, the specific power input and the size of which are smaller than the former. Bases of calculations as well as diagrams for economics in power requirements as a function of temperatures are furnished; these are generally valid for all types of coolants. Gy. Faragó  
*Courtesy of Hungarian Technical Abstracts*

111.00, 17.

"The calculation, maintenance, and economy of luminous tube lighting" ; p. 17, (EIS)-  
TECHNOL, Vol. 16, no. 3, March 1953, Budapest, Hungary)

SC: Monthly List of East European Accessions, L.O., Vol. 1, No. 11, Nov. 1953, Incl.

FARAGO, Gy.

"Modern Light Sources; Fluorescent Lamps", P. 116, (VILLANOVAG, Vol. 2, No. 4, April 1954, Budapest, Hungary)

CO: Monthly List of East European Accessions (FEAL), LC, Vol. 4, No. 3, March 1955, Uncl.

FARAGO, Gy. - Magyar Energiagazdasag - Vol. 8, no. 6, June 1955

Modern condensers in cold-storage plants. p. 225

SO: Monthly list of East European Accessions, (EEAL), LC, Vol. 4, No. 9, Sept. 1955  
Uncl.

FARAGO, GY.

Mechanization of polishing plane surfaces with water;  
an innovation. p. 168  
FAIPAR (Faipari Tudomanyos Egyesulet) Budapest  
Vol. 6, no. 6, June 1956

Source: EEAL - LC Vol. 5. No. 10 Oct. 1956

FARAGO, GY.

New method of using heat pumps with refrigeration. P. 121  
MAGYAR ENERGIAGAZDASAG Budapest, Vol. 9, no. 4, Apr. 1956

SOURCE: East European Accessions List (EEAL) Library of Congress  
Vol. 5, no. 8, August 1956

FARAGO, Gy.

Design contest for lighting soccer stadiums and the field of the People's Stadium. P. 29 Beginning of work in the Martonvasar Agrometeorologic Observatory. P. 32 Automatization of the Manufacturing of motorcycles. P. 3 of cover. MUSZAKI ÉLET (Muszaki és természettudományos Egyesületek Szövetsége) Budapest Vol. 11 No. 2, Jan 1956

SOURCE: EEAL LC Vol. 5, no. 7, July 1956

~~FARAGO, GY.; MAROTI, GY.~~

Modern lighting fixtures. p.81

VILLENCSA. Budapest, Hungary. Vol. 7, no. 3, Mar. 1949.

Monthly List of East European Accessions (EEAI), LC. Vol. 8, No. 9, September 1959  
Uncl.

FARAGO, Gyorgy, "I.o.Rovidhullamu Amator".

$\pi$ -filtering motive stage. Radiotekhnika 10 no.10:303-304  
0 '60.

FARAGO, Gyorgy ( Budapest)

A TV service case. Radiotechnika 10 no.4:112 Ap '60.

<sup>A</sup>  
FAROGG, Gyorgy, I. (HA 5 BG) osztalyu rovidhullamu amator.

Shortwave final degree by the GU 29 tube, Radiotechnika  
11 no.3:72-73 Mr '61

FARAGO, Gyorgy, okleveles gepeszmernok

Open-air illumination of industrial plants. Villamosag 10 no.6:177-182 Jo '62.

1. Vegyimuveket Tervezo Vallalat vilagitastechnikai szakertoje.

KNAPP, Oskar, a muszaki tudományok doktora; FARAGO, Gyorgy

Industrial lighting. Elet tud 15 no.32:1003-1006 7 Ag  
'60.

FARAGO, Gyorgy, I. osztalyu rovidhullamu amateur (HA 5 BG)

Multiband "trap" antennas. Radiotechnika 11 no.6:170-171  
Je '61.

FARAGO, Gyorgy (HA 5 BG)

Collins-filter without wave changer. Radiotechnika 12 no.9:284-  
285 8 '62.

FARAGO, Gyorgy, ~~ak~~leveles gepeszmernok

Illumination of the open-air parts of industrial plants.  
(To be contd.) Villamosag 10 no.5:139-144 My '62.

1. Vegyimuveket Tervezo Vallalat vilagitastechnikai  
szakertoje.

FARAGO, Gyorgy

Lighting of open-air work-places. Musz elet 17 no.8:14 Ap '62.

FARAGO, Gyorgy, (HA 5 BG)

Ultrashort wave converter. Radiotekhnika 13 no.5:172 My '63.